

Specifications

Model		Z232KW-42	Z242KH-48	Z252KH-54	Z242KW-48	Z252KW-54	
Engine	Type	Air cooled 2cylinders gasoline engine					
	Engine gross power	HP	21.5*	22.0**	25.0**	21.5**	24.0**
	Total displacement	cu.in. (cc)	44.3 (726)	44.2 (725)	45.6 (747)	44.3 (726)	44.3 (726)
Dimensions	Overall length	mm	1890	2006			
	Overall width (w/ mower)	mm	1400	1552	1710	1552	1710
	(w/o mower)	mm	1076	1207			
	Overall height (w/ ROPS)	mm	1693	1855, Fixed ROPS		1738, Foldable ROPS	
Wheel base		mm	1236	1195			
Tread	Front	mm	616	826			
	Rear	mm	885	964			
Tire size	Front		11 x 4 - 5 pneumatic		13 x 6.5 - 6 pneumatic		
	Rear		18 x 7.5 - 10		22 x 10 - 14		
Weight (w/mower & fuel)	kg		292	368	375	383	390
Transmission			Hydro-Gear® ZT-2200		Hydro-Gear® ZT-3100		
Transmission system			2-HST w/ Gear reduction				
Speed control			2-hand lever				
Travel speed range	Forward	km/h	0 - 10.5		0 - 12.9		
	Reverse	km/h	0 - 6.4				
Braking system			Cog style parking lock / Hand lever				
PTO	Type		Belt drive				
	Clutch type		Electric clutch				
	PTO brake		Dry disc				
Mower deck	Model		RCK42P-122Z	RCK48P-200Z	RCK54P-200Z	RCK48P-200Z	RCK54P-200Z
	Mower deck type		Side discharge				
	Mower lift system		Mechanical		Mechanical / Foot pedal K-LIFT Ratchet System		
	Deck depth	mm	114		127		
	Drive type		Belt drive				
	Deck steel thickness	mm	3.4, 10Ga				
	Anti-scalp roller		Rigid				
	Cutting width of mower	in./mm	42 (107)	48 (1219)	54 (1372)	48 (1219)	54 (1372)
	Number of blades		2		3		
	Cutting height	in./mm	1.5" - 4.25" (38 - 108) 1/4" increments		1.5" - 4.5" (38 - 114) 1/4" increments		
	Mounting system of mower		Parallel linkage				
	Blade tip speed	fpm (m/s)	17700 (89.8)		18100 (92.0)		
Seat			21" high back seat w/ armrests		21" high back seat w/ armrests		
Seat suspension			N/A		OPT		STD
Engine start			Key switch		Push switch		
Fuel tank capacity	ltrs		13.6		16.3		
Battery			U1 (12V, RC : 45min, CCA : 300, CA : 410)				
Hour meter			Hour meter		Hour meter w/ maintenance indicator		
Fuel gauge			Sight window				

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

**Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment. Please contact your local Kubota dealer for warranty, safety or product information.

Attachment & Option Kit



• **Grass catcher**
Easily attach or detach the grass catcher in minutes without the use of tools.



• **Mulching kit**
• **LED work light kit**
• **Suspension seat kit*1**
• **Hitch kit*2**
*1 Z242KH, Z52KH only
*2 Z232KW only
(Standard on Z242KH, Z252KH, Z242KW, Z252KW)



©2022 Kubota Corporation

Kubota Australia Pty Ltd
25-29 Permas Way, Truganina VIC, 3029 Australia
Freecall: 1800-334-653
Email: sales@kubota.com.au
Web Site: <http://www.kubota.com.au>

Kubota New Zealand Limited
433 Rangitikei Street, Cloverlea, Palmerston North, 4412 New Zealand
Freecall: 0800-582-682
Email: sales@kubota.com.au
Web Site: <http://www.kubota.co.nz>



For Earth, For Life
Kubota

KUBOTA ZERO-TURN MOWER

Z200 Series Z232/Z242/Z252

Enhanced style, comfort, convenience, and performance in three new residential zero-turn mowers.



The new Z200 Series. Smooth, effortless performance for a wide range of residential mowing jobs.

The new Z200 Series is designed for homeowners who want comfort and performance in an easy-to-operate zero-turn mower. All three Z200 Series mowers offer a wide range of advanced features that let you maneuver quickly and effortlessly across landscapes and around objects in comfort and style.



**Z242KW / Z252KW
with 48", 54" decks**



**Z242KH / Z252KH
with 48", 54" decks**



**Z232KW
with 42" deck**

COMFORT & CONVENIENCE EASY OPERATION

From their attractive styling and enhanced convenience to their powerful performance and ergonomic operation, the Z200 series offers an all-new residential mowing experience.

Powerful Engines

Power—and plenty of it—gives the Z200 Series the ability to handle a wide range of residential mowing jobs.



Z232KW/Z242KW/Z252KW models
(Powered by Kawasaki® FR series)
21.5HP/21.5HP/24.0HP



Z242KH/Z252KH model
(Powered by KOHLER® 7000 Series)
22.0HP/25.0HP

High strength steel Deep Welded Mower Deck

This high strength steel, welded mower deck provides outstanding, professional-level cutting performance. If you're a homeowner who wants the best—this mower deck is for you.



Support for Improved Durability

Wide and Deep Groove Pulley



Wide Tread

Wide-tread tires provide better traction and reduced weight distribution to help protect your lawn.

K-RIDE Comfort System



533 mm High Back Seat and 38 mm Stroke Suspension*

Thick and wide high back seats and 38 mm stroke suspension help absorb the impact from the ground, allowing the operator to work comfortably for hours at a time. *Suspension seat standard for Z242KW-48 & Z252KW-54 model only.

HST Lever Vibration Reduction

A newly designed HST lever reduces lever vibration and increases operator comfort.

Step Vibration Reduction*

Thick rubber cushions under the step plate also help reduce vibration. *Standard for Z242 & Z252 models only.



Model	K-RIDE Comfort System		
	HST Lever Vibration Reduction	Step Vibration Reduction	Suspension Seat
Z232KW	●	-	-
Z242KH/Z252KH	●	●	-
Z242KW/Z252KW	●	●	●



PERFORMANCE YOU CAN DEPEND ON

With powerful engines, rugged transmissions, and strong frames, the new Z242 and Z252 features are ready to tackle even the toughest residential mowing jobs.

A. Front Tire

"Pro" style front tires for "pro" style mowing results.



B. Mower Lift Pedal Force

Improved design requires less effort to raise and lower the mower deck.



C. Toolless Step Removal

Quickly remove the step to access the mower belts.



E. Toolless Pulley Cover Removal

Easy access simplifies pulley maintenance.



F. Engine Start Push Switch

Easy one-handed operation of the choke and engine start switch.



Right side operation panel



G. Storage Box with Cover

The cover keeps out dust and prevents the contents from falling out.



D. K-LIFT (Mechanical One Push Deck Lift Pedal)

The K-Lift pedal makes adjusting the cutting height simple.



1 Push and release the pedal to raise the deck



2 Use the dial to adjust the cutting height



3 Push and release the pedal again to lower the deck

H. Foldable Rops

The ROPS easily folds down to allow to pass under low obstructions, as well as permits easier storage in a garage or shed. (Standard for Z242KW-48 and Z252KW-54 model only.)

I. New Design Fender / Rear Cover

A rugged look that suggests durability and professionalism.



J. New Rear Wheel Design

Bold and robust, the rear wheel complements the Z200 Series overall appearance.

