



DRIP HOSE BOOMS



Precision, Productivity, Performance.



Precise spreading onto soil surface
Standard and telescopic models
High spreading output rates

DRIP HOSE BOOMS - 9 > 18 M

For precise spreading on growing crops

THE ADVANTAGES OF OUR DRIP HOSE BOOM

- Fully galvanised structure
- Respect of the plant cover
- Spreading on growing crops
- Reduced nitrogen loss
- Maximum value out of organic fertiliser
- Minimum smell
- Even transverse distribution
- Uniform volume spread on soil surface

BOOM FUNCTIONS


In-cab simplified controls for:

- Boom arms opening/closing
- Hoses folding/unfolding (*no leaks during transport*)
- Telescopic function opening/closing (*if option*)
- Hydraulic locking

ADVICE FOR BEST USE

The hose ends must touch the ground at all times when spreading.

- Higher value out for fertiliser
- Reduce nitrogen loss
- Low contamination of crops



VERTICAL DISTRIBUTOR

- Ideal for spreading thick slurry
- Foreign bodies caught in the stone trap
- Optimise distribution of slurry
- Even outlet distribution



HALF-WIDTH SECTION CUT-OFF

- Feeding of right or left side of the boom
- Facilitate end of spreading operations
- Prevent overlapping
- Maximum spreading accuracy



PART-WIDTH SECTION CUT-OFF(S)

- Manual valve cut-off
- Standard on telescopic booms
- Optional behind the wheels
- Prevents overdosing



ACTIVE SLOPE COMPENSATION

- Boom always parallel to the ground
- Perfect distribution across the entire working width
- Reduced load on the boom structure

FEATURES

Working width	Number of outlets	Hose diameter	Number of macerator(s)	Space between hoses
9	30	Ø40/50	1	31 cm
12	40	Ø40/50	1	30 cm
12/15	48	Ø40/50	2	32/39 cm
15	48	Ø40/50	1	32 cm
15/18	48	Ø40/50	2	38/41 cm
18	48	Ø50	1	38 cm